

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

Amendment to the Claims:

This listing of claims replaces all prior versions, and listings, of claims in the application:

1. Canceled.

2. **(Currently Amended)** A method as in claim 11 [[1]] further comprising:
transmitting, prior to the receiving, information including the first packet on the input optical signal, the transmitting including reserving the reserved wavelength buffer.

3. **(Currently Amended)** A method as in claim 11 [[1]], further comprising receiving an additional input optical signal having a second packet of information wherein the second packet of information is carried within the additional input optical signal over substantially the channel on which the first packet is received.

4. **(Currently Amended)** A method as in claim 11 [[1]], further comprising:
prior to transmitting the first packet of information on the output optical signal, extracting label information from the

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

input optical signal, the label information including
information about the first packet of information;

generating a control signal according to at least a portion
of the label information;

controlling a signal-producing component to reproduce the
first packet of information within the output optical signal in
the active wavelength buffer; and

re-associating the label information with the first packet
of information.

5. (Previously Presented) A method as in claim 4, wherein
the label information is carried within the input signal in a
channel distinct from an input channel that carries data and
distinct from the reserved wavelength buffer and within the
output signal in a channel distinct from the active wavelength
buffer.

6. (Previously Presented) A method as in claim 4, wherein
the signal-producing component comprises:

a local oscillator controlled by the control signal to
produce a local oscillator signal, and

a modulator, accepting as one input, the local oscillator
signal, and as another input, a signal representing the first

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

packet of information, the modulator further producing as an output, a modulated output signal including the first packet of information.

7. (Original) A method as in claim 6, wherein a frequency of the local oscillator signal corresponds to a difference in frequency between the channel on which the first packet is received and the active wavelength buffer.

8. (Original) A method as in claim 6, wherein the modulator is a Mach-Zehnder modulator.

9. (Original) A method as in claim 4, wherein the signal-producing component comprises:

a laser, controlled according to the control signal to produce a laser signal, and

a semiconductor optical amplifier, accepting as one input the laser signal, and as another input a signal representing the first packet of information, the semiconductor optical amplifier further producing as an output, a modulated output signal including the first packet of information.

10. Canceled.

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

11. (Currently Amended) A method comprising:
receiving a first packet of information on an input optical
signal that occupies a plurality of input channels, each input
channel being included in one among an input plurality of
distinct wavelength ranges that are respectively in selected
International Telecommunication Union (ITU) WDM windows; and
transmitting the first packet of information on an output
optical signal that occupies a plurality of output channels,
each output channel being included in one among an output
plurality of distinct wavelength ranges,
wherein the plurality of input channels includes at least a
plurality of WDM channels within one ITU WDM window which
comprise:
(A) a reserved wavelength buffer selected from one of
the plurality of adjacent WDM channels within the one ITU WDM
window; and
(B) a channel on which the first packet is received,
wherein the plurality of output channels includes an active
wavelength buffer on which the first packet is transmitted, and
wherein each among the input plurality of wavelength ranges
is associated, in order of increasing wavelength, with one among
the output plurality of wavelength ranges in order of increasing

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

wavelength, the wavelength range including the reserved
wavelength buffer being associated with the wavelength range
including the active wavelength buffer,

~~A method as in claim 1, further comprising:~~

wherein the method further comprises:

extracting label information, the first packet of
information, and a carrier from the input optical signal;
producing a first electronic signal representing
information from the first packet of information; and
producing a second electronic signal representing the label
information,

wherein transmitting the first packet of information
further comprises modulating the carrier with the first and
second electronic signals to produce the output optical signal.

Claims 12-30: Canceled.

31. (Previously presented) A device, comprising:

an optical input port to receive a wavelength-division
multiplexed (WDM) signal having a plurality of different WDM
channels within each single International Telecommunication
Union (ITU) WDM window, wherein at least one of the WDM channels
is empty and is reserved as a buffer channel;

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

an optical splitter to split the received WDM signal into first, second and third optical signals;

a label processing module to process label information in the first optical signal to produce a first electrical control signal having new label information for a channel shifting arrangement;

an optical filter to filter the second optical signal to remove modulation bands thereon to produce an optical carrier signal;

a data signal regenerator to receive the third optical signal to process data in each WDM channel in the third optical signal to generate a second electrical control signal having data in the received WDM signal; and

an optical modulator to modulate the optical carrier signal in response to the first and the second electrical control signals to shift a selected WDM channel to the buffer channel according to the channel shifting arrangement to produce a new WDM signal.

32. (Previously Presented) The device as in claim 31, wherein the signal regenerator comprises:

an optical filter to filter and remove label information from the third optical signal;

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

an optical receiver to convert the filtered third optical signal into an electrical signal having input data;

an electronic signal regenerator to generate an electrical data signal having the input data; and

a modem to produce the second electrical control signal in response to the electrical data signal.

33. (Previously Presented) The device as in claim 32, wherein said electronic signal generator is coupled to receive an input from the label processing module and to drop input data of a selected WDM channel in response to the input.

34. (Previously Presented) The device as in claim 31, wherein the label processing module comprises:

an optical receiver to convert the first optical signal into a first signal;

a label processor to process the first signal and to produce a new label;

a label writer to produce a label writing signal in response to the new label; and

a modulator to produce the first electrical control signal in response to the label writing signal.

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

Claims 35-48: Canceled.

49. (Previously presented) A method, comprising:

separating a received wavelength-division multiplexed (WDM) signal comprising a plurality of different WDM channels within a single International Telecommunication Union (ITU) WDM window into a first optical signal carrying a WDM channel that has label information of the WDM channels, and a second optical signal at an optical carrier frequency without WDM channels, and a third optical signal comprising WDM channels carrying data and at least one empty WDM channel which is reserved as a buffer channel;

converting the third optical signal into an electronic data signal wherein a signal channel corresponding to a selected WDM channel is shifted to a signal channel that corresponds to the buffer channel;

converting the first optical signal into an electronic label signal which has new label information to reflect updated channel information after channel shifting in the electronic data signal; and

modulating the second optical signal to produce a new optical WDM signal having WDM channels therein which carry a new label channel with the updated channel information and data.

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

50. (Previously presented) The method as in claim 49, further comprising dropping data of a WDM channel and adding new data to the dropped WDM channel as a new WDM channel in the electronic data signal so that the new optical WDM signal carrying the new WDM channel.

51. (Previously presented) The method as in claim 49, wherein the WDM signal is an optical single sideband (OSSB) modulation signal and different WDM channels and a channel carrying the label information are different modulation bands in the OSSB modulation signal, and the method comprising performing an OSSB modulation on the second optical signal to produce the new optical WDM signal.

Claims 52-62: Canceled.

63. (Previously presented) A method, comprising:
receiving an optical wavelength-division multiplexed (WDM) signal having an optical carrier and WDM channels at WDM channel frequencies different from the optical carrier in an optical WDM network,

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

separating the received WDM signal into a first optical signal carrying a WDM channel that has label information of the input WDM signal, and a second optical signal which is the optical carrier only, and a third optical signal comprising WDM channels carrying data;

converting the first optical signal into an electronic label signal which has label information of the WDM channels in the received WDM signal;

optically filtering the third optical signal, in response to a control signal generated from the electronic label signal, to produce a filtered third optical signal that carries a selected WDM channel;

converting the filtered third optical signal into an electrical signal to extract data of the selected WDM channel and to make the selected WDM channel available for carrying data; and

modulating the second optical signal to carry a new WDM channel and a new WDM label channel, wherein the new WDM label channel includes channel information of the new WDM channel.

64. (Previously presented) The method as in claim 63, wherein the new WDM channel and the selected WDM channel are at a same WDM channel frequency.

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

65. (Previously presented) The method as in claim 63, wherein the new WDM channel and the selected WDM channel are at different WDM channel frequencies.

66. (Previously presented) A device, comprising:

an optical input port to receive an optical wavelength-division multiplexed (WDM) signal having an optical carrier and WDM channels at WDM channel frequencies different from the optical carrier,

an optical element to separate the received optical WDM signal into first, second and third optical signals;

a label processing module to process label information of the received optical WDM signal in the first optical signal to produce a first control signal;

a first optical filter to filter the second optical signal to remove any modulation bands thereon to produce a filtered second optical signal which includes the optical carrier only;

a second optical filter to filter the third optical signal, in response to the first control signal, to produce a filtered third optical signal that carries a selected WDM channel;

Applicant : Winston I. Way
Serial No.: 09/755,136
Filed : January 8, 2001

Attorney's Docket No.: 14723-004001

a signal regenerator to extract data of the selected WDM channel to produce a dropped signal containing the extracted data; and

an optical modulator to modulate the filtered second optical signal to carry a new WDM channel and a new WDM label channel, wherein the new WDM label channel includes channel label information of the new WDM channel.

67. (Previously presented) The device as in claim 66, wherein optical modulator modulates the filtered second optical signal to place the new WDM channel at the same WDM channel frequency as the selected WDM channel.

68. (Previously presented) The device as in claim 66, wherein optical modulator modulates the filtered second optical signal to place the new WDM channel at a WDM channel frequency different from the selected WDM channel.